

Mecal S.r.l.  
Strada per Felizzano 18  
I - 15043 Fubine (AL)  
ph. +39 0131 792792  
fax +39 0131 792733/4  
www.mecal.net



# TT Crimping Press



## Specifications

**ID**  
TT

**POWER**  
0.55 Kw (0.75 HP)

**FORCE**  
2000 Kg (4450 lb)

**STROKE**  
40 mm (1.57")

**CRIMPING HEIGHT  
(Bottom Dead Center)**  
135.8 mm (5.34")

**WEIGHT**  
41 Kg (95.6 lb)

**DIMENSION (mm)**  
W 200 x H 580 x D 300

**DIMENSION (")**  
7.9 x 23 x 11.8

**CONFIGURATION**  
bench top / automatic

**POWER SUPPLY**  
different arrangements  
available

**SURFACE FINISHING**  
RAL 7038 light grey



The TT Crimping Press is available either in semi-automatic (for bench-top use) configuration or in full automatic (integrated into a cut and strip machine) configuration. Very compact and light, its spheroidal cast iron, one-piece structure offers the highest rigidity for a very stable crimping height value. The standard stroke is 40mm, but other different strokes are available upon request. The 135.8mm  $\pm$  0.02mm crimping height (measured from the applicator base plate to the press T-coupling when at Bottom Dead Center) allows the TT to accept all the mini-style applicators fitted with the standard T-coupling. Upon request, a crimping height continuous regulating system ("TAC TAC") can be supplied. A proprietary safety cover (standard issue on the semi-automatic configuration) grants the operator a perfect view of the crimping zone while enjoying complete protection from any hazard. Mecal's own CFA crimp force analyser can be fitted as an option. The semi-automatic configuration (for bench top use) always includes safety cover, reel arm, foot switch according to the international safety standard and CE regulation.

*Produced under a quality Management System certified to ISO 9001 and 14001 (TÜV).*

Specifications subject to change. Consult Mecal S.r.l. for latest specifications.