

UP 35 | SSC

genuine and solid

WEZAG



Features

Technical data

20 kN Crimp Force | Pneumatic | Air pressure 6 bar | 87 PSI

Process-safe

Due to forced sequence control and with linear crimping movement, ideal for use in automotive and industrial applications

Application range

Uninsulated contacts up to 16 mm² | Insulated terminals up to 10 mm² | Wire end ferrules up to 50 mm² | Automotive connectors up to 10 mm²

Different

UP 35 BA with contact hold function, no hands in the working area due to additional lever (mountable for left and right-handed users), ideal for miniatur plugs < 0,14 mm²

High-quality

SSC with safety function - working without finger protection, operate contact hold function with double foot pedal, no hands in the working area

Flexible

React to different production orders with tool-free quick-change adapter system

Portable

25 kg weight, space saving design and portable to any place and immediately ready for use

Reliable

The production quantity is recorded by the electronic piece counter

Individual

Different adapters allow almost unlimited variability for individual customer solutions, use of external dies possible

Varied

A selection of standard processing solutions with and without positioning system available from stock

User-friendly

Safety or two-hand operation optionally available

Customized

Customized versions in design and function are available on request

Reliable

Quality Made in Germany and CE compliant

Versions

Pneumatic Crimping Machine UP 35

Linear working mechanism (standard version).

Pneumatic Crimping Machine UP 35 | BA

Linear working mechanism. With integrated contact holding system operated manually by hand lever.

Pneumatic Crimping Machine SSC

Linear working mechanism. Can be operated without finger guard and with double foot pedal.